

SPECIFICATIONS

All-in-One Video Conferencing Solution for Unparalleled Collaborations



reddot award 2019
best of the best

*D7 in this image is not in 1:1 ratio



PRODUCT	D7 55"
SOFTWARE	DTEN D7 OS, provisioned by D7 OS
ALL-IN-ONE D7	LED 55" Multi-Touch Display 4K Camera 16-Microphone Array Integrated Speakers
DISPLAY	LED 55" , 4K , 16:9 Capacitive Touch Screen
CAMERA SYSTEM	Fixed Lens, Infinite Focus F-value: 2.8 4K Diagonal Field of View (FOV): 86-Degrees, Adjustable to 120-Degrees Unit Mounted Tilt: 15 Degrees
AUDIO SYSTEM	16 Elements Microphone Array Integrated 2-Channel Stereo Speakers High Quality 20-kHz Audio Zoom Rooms Acoustic Echo Cancellation Automatic Gain Control (AGC) Automatic Noise Reduction
NETWORK	Ethernet (RJ-45) 100/1000 Mbps Wi-Fi 802.11a/b/g/n, 802.11ac (2.4 and 5 GHz) IPv4 Dynamic Host Configuration Protocol (DHCP)/ Static HTTP Proxy Support

INPUTS AND OUTPUTS	HDMI Out x 1 USB 3.0 x 1 3.5-mm Audio Jack x 1 Microphone x 1 Ethernet LAN (RJ45) x 1
POWER	Auto-Sensing Power Supply 100 to 240 VAC, 50 to 60 Hz
VESA	400 x 300 mm
PRODUCT DIMENSIONS	49 x 30.5 x 2.13 in (124.49 x 77.38 x 5.42 cm)
PRODUCT WEIGHT	50.7 lb (23 kg)
PACKAGE DIMENSIONS	56 x 36 x 8.5 in (142 x 92 x 21.5 cm)
PACKAGE WEIGHT	77 lb (35 kg)
OPERATING TEMPERATURE AND HUMIDITY	Operating Temperature 0°C to 40°C Storage Temperature -10°C to 60°C Operating Humidity 20% to 80% RH Storage Humidity 10% to 60% RH
LANGUAGE SUPPORT	English * Additional languages to be supported in future software release
SYSTEM REQUIREMENT	Zoom Rooms License
APPROVALS AND COMPLIANCE	FCC, CE, CCC, ROHS, ACMA, CB PSE, TELEC, BIS (Pending)

*Specifications are subject to change without prior notice.

Zoom Rooms Simplified Affordable

Don't hesitate to contact us.
+49 40 180 424 7400 or info@elink-distribution.com



eLink Distribution AG